

**COMMODITY LIST**

**RFQ: GS1039.PPPFA.T3.04.2021**

**Price Validity Period: 27 April 2021 – 27 April 2022**

ITEM	STANDARD	UNIT	PRICE
<b>PPE</b>			
Red Overalls (2 piece) Standard Red Conti Suits	SABS	Each	
Safety Boots Frams Geo-trek 4911,	NRCS – SANS 2035	Per Pair	
Disposable Overalls 80GSM, SABS approved -90CM Zipper	SABS	Each	
Ear Plugs (Sonic PP)	SABS	Each	
Tyvek Disposable Overall Type 5/6	Dupont Tyvek EN STANDARD	Each	
Dust Masks - Pioneer or Nikki (FFP 2 and 3)	SANS, SABS or EN149-1001	Each	
Clear Goggles (DV326BC)	DROMEX	Each	
Comarex Hand Gloves (Yellow) G-COM	Comarex	Each	
Gloves (Long Welding) -Type -WELD-6-GR	DROMEX -SABS	Each	
Dust Masks 3M (FFP 2 and 3)	SABS	Each	
Gloves - (Long PVC) GPVC35	DROMEX	Each	
Dark Spoggles (DV326BC)	DROMEX	Each	
Disposable overalls - Tyvek or 80gsm spunbond	SABS	Each	
<b>CONSUMABLES</b>			
Drill Bits - 3.2mm double ended	SOMTA	Each	
Drill Bits - 4.8mm double ended	SOMTA	Each	
Rivetts - 3.2mm x13mm Mild steel	Galv	Each	
Rivetts - 4.8mm x18mm Mild steel	Galv	Each	
Self-Tapping Screws - 8mm x 13mm S/ steel	Standard Product	Each	

Strapping Buckles - 19mm (bag 1000)	Galv Z275	Bag 1000	
Strapping Bands - 19mm (50kg)	stainless	Per Roll	
Posi Screws - 8mm x 30mm Mild steel	Standard Product	Each	
19mm Bonnet Washers	Standard Product	Each	
Binding Wire - 1.6mm Galv (50kg)	Z275	Per Roll	
Plastic Bags (refuse) - 40 micron	SABS	Each	
Plastic Bags (Asbestos) - 150 micron Yellow	SABS	Each	
Micron Plastic sheet - 250-micron 30m x 3m wide	SABS	Per Roll	
Barricade Nett Rolls - 1m wide x50m (Yellow and Orange)	Mesh 25mm x10mm	Per Roll	
Membrane - (fibreglass Mesh) 10x10, 1m x 100m	EN-12654 (ISO 5084)	Per Roll	
Foster Sealer P2191	P2191	Per Tube	
Cutting Disks - 4.5" (Steel)	Pferd	Each	
Cutting Disks - 9" (Steel)	Pferd	Each	
<b>MISCELLANEOUS</b>			
Membrane - (fibreglass Mesh) 10x10, 1m x 100m	Thread_count per 1cm, 19 + 1-0, 11 +/-0.5. Tensile Strength min N/5 cm 5500/2500. Service Temperature up to 600°C . Thickness, 0.37 +/-0.02mm	Per Roll	
Ceramic Fibre Blanket	Density: 96kg/m3 and 128kg/m3 Dimensions: 610mm wide Operating Temperature: 1260 deg C Thermal Conductivity: At 600 deg C, 0.155-0.20 w/m.k Tensile Strength: 0.4.5 Mpa Shot Content: less than 12% Composition: Al2O3 46% Al2O3 + SiO2 97% Fe2O3 1.2%	Per Roll	

Insulation Rope	Size 6, 10, 13,16, 20, and 25mm diameter x 30m long. Construction Material E- Glass Working Temperature up to 550°c	20m Roll	
Water Base Metal Primer (RB-10 High performance)	RB-10 / 4-NS4	5 ltr	
Netting Wire - (900mmx13mm Mesh) 30m Roll	Galv Z275	Per Roll	
TPH Plaster	TPH 300 is a multi-purpose non asbestos plaster supplied in 40kg bags in a dry powder form. When mixed with clean water, it dries to a smooth dust free, hard, water resistant finish. No protection from the elements is necessary. If so desired, it may be painted and can be used both indoors and outside. Thermal Conductivity 100° c 0.08W/m -250° c 0.09W/m Covering 5m <sup>2</sup> at 6mm thick. Working Temperature -20°c to 300°c	Each	
Marques tent	White, removable side panels, 9m x 18m	Each	
Construction Portable Additive Flush Toilet Hire	Per unit per month 1 to 31 Days	Each	
Damage Waiver Toilet	Per unit per month- this covers the small repairs on units	Each	
Monthly service of Toilet	Two services per week	Each	
Once off emptying of septic tank		Each	